

QATOL UTTO WET BRAKE OIL SAE 10W30

QATOL UTTO WET BRAKE OIL SAE 10W30 is a multifunctional transmission and hydraulic fluid for tractors and plant. Its Next generation technology has much improved the performance abilities of heavy-duty equipment in terms of load, speed, control, and reliability through innovative powertrain designs. These designs have changed and increased the requirements of powertrain fluids to deliver higher levels of performance and productivity while reducing operating costs. Friction control, wear protection, thermal stability, shear stability, rust and corrosion protection, and pumpability are features that must be optimally balanced to provide extended clutch life, maximum drawbar loading, and maintain operations on uneven terrain over a wide range of ambient temperatures. QATOL UTTO SAE 10W30 delivers exceptional performance in today's powertrain transmissions, drive axles, clutches, PTOs and hydraulic systems.

SPECIFICATIONS

QATOL UTTO WET BRAKE OIL SAE 10W30 meets and exceeds the following performance levels.

- Case New Holland MAT3525
- Caterpillar TO-2
- Dennison HF-0/1/2
- API GL-4
- Ford M2C86-B/C, 134-D, 1207
- John Deere J20 A-C
- Komatsu AXO80
- Kubota UDT
- Massey Ferguson M1135/1143/1145/1127A
- New Holland 410B
- Sperry Vickers M230-S, M2950S, I-280-S
- Volvo WB101
- ZF 03E, 05F, 06K, 17E, 21F

KEY BENEFITS

- Excellent anti-squawk properties.
- Suitable for nearly all hydraulic, transmission and differential systems.
- Excellent thermal and oxidation stability.

KEY PROPERTIES

PROPERTIES	TEST METHOD	UNIT	SAE 30
Appearance	Visual	-	Clear & Bright
Kinematic Viscosity @ 40°C	ASTM D445	cSt	64.76
Kinematic Viscosity @ 100°C	ASTM D445	cSt	10.21
VI	ASTM D2270	-	146
Flash Point, COC	ASTM D92	°C	220
Pour Point	ASTM D 97	°C	-39
Density @ 35°C	ASTM D4052	g/ml	0.857

HAZARDS

This oil used as recommended and for the application for which it has been designed does not present any particular health & environmental risk.

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to Material Safety Data Sheet.

PACKING

Available Packages: 1000L,208L,60L,20L, 5L, 4L,1L